

RICH PUTTY™

TEXTURED

RICH PUTTY™ is water-based textured wall putty for exteriors. It provides a very strong durable foundation and brings out the best performance from the finish paints, both in looks and in durability. It can be used to form various pattern.

FEATURES AND BENEFITS:

- Textured putty has a unique formulation that makes it a long lasting, protective and decorative finish, suitable for tropical Indian climatic conditions.
- It is specially formulated using excellent quality Quartz with controlled particle size distribution, excellent optical properties, chemical inertness etc.
- It is quick drying, thus ensuring faster completion of jobs
- It has better alkali resistance, thus making it more suitable for new walls
- It can form various pattern using frame.
- Ready to use

USES:

As a Finish/Base Coat Over

Concrete – priestesses, plastered, POP, stucco finishes.

PREPARATION:

Clean area removes all unsound material, grease, oil, paint and any other foreign materials that will inhibit performance. Remove excess surface water and puddles prior to use.

PLACEMENT:

It is advisable to apply thin even coat of Textured Putty to insure maximum coverage of the substrate and performance of the system.

Application with Putty Knife:

Textured Putty should be applied in the walls evenly to provide a total wet film thickness of 3mm using putty knife. Also made into different patterns using frames.

Note:

Always work in shade during hot weather. Stop only at natural breaks in the walls or at corners.

CURING

Textured Putty dries and cures through the evaporation of water and coalescing to form a base. Drying will be dramatically extended in cool damp weather. Supplemental indirect heat will be necessary at or below 10°C to insure proper curing. Depending on temperature, humidity and wind conditions.

COVERAGE:

On normal masonry surface by knifing
80 – 100 sq ft./bag of 25kg

Coverage may vary considerably depending on the substrate conditions (rough or smooth), finishing technique used, and the application thickness.

PACKAGING:

Available Pack sizes - 25kg

SHELF LIFE:

Six months from date of manufacture.

LIMITATIONS:

- **Do Not** allows freezing.
- **Do Not** apply over substrates that are frozen or contain frost.
- **Do Not** use Textured Putty on horizontal substrates, roofs, swimming pools or where standing water is likely to occur.

LIMITATIONS (Contd.):

- **Do Not** apply when atmosphere or substrate temperature is below 10°C or above 40°C.
- **Do Not** apply when humidity is below 10% or above 80%.
- **Do Not** add or mix any materials with the putty unless approved by the **W.R.Bonsal & O'Connors India**.
- **Do Not** store below 10°C or above 40°C.
- **Do Not** apply when substrates containing pyrite (iron sulphide)
- **Do Not** use over epoxy, urethane or high gloss surfaces.
- **Do Not** apply if rain is forecast within 24 hours.
- **Do Not** apply over concrete cured less than 28 days.

CAUTION: Contains Acrylic polymer, and preservatives. Irritant. Avoid contact with eyes or prolonged contact with skin. In case of contact, flush thoroughly with water. For eyes, flush thoroughly with clean water for at least 15 minutes and get prompt medical attention. Do not inhale. In case of inhalation move to fresh air and seek medical attention. Empty container may be hazardous to children. **KEEP OUT OF REACH OF CHILDREN.**

LIMITED WARRANTY: W.R. Bonsal & O'Connors India warrants that this product and the materials used therein meet or exceed the applicable standards listed and enforced at the time of manufacture. Company will replace any product or part, which proves defective due to quality of ingredients used or due to the manufacturing process itself. This warranty shall apply only if the product is used in strict accordance to applicable specifications and instructions provided by Bonsal for its use, and company shall not be liable otherwise. Replacement of any defective product, or, Bonsal option, refund of the purchase of any defective product shall be the be the buyer's sole remedy under this Warranty, and Bonsal shall in no event be liable for any damages in excess of the purchase price of the defective product. **W.R.BONSAL & O'CONNORS SHALL IN NO EVENT BE LIABLE FOR ANY CONSIQUENTIAL, INCIDENTAL OR SPECIAL DAMAGES.**

W.R. BONSAI & O'CONNORS INDIA
#22, KAMARAJAR SALAI, KODUNGAIGUR,
CHENNAI – 118. Ph. : 044-25588485.
Email : henryraj_raj@yahoo.com.